

PURO MINI[®]

Compressed air condensate separation

The PURO range of oil/water separators separates oil from condensate, generated by compressed air systems. The PURO uses a specially designed filter, instead of a weir, to remove the bulk of the oil and any type of condensate drain may be applied.

The **PURO MINI** covers all compressor capacities up to **3.5m³/min (125 cfm)**.

The separation method of the **PURO MINI** is the same as its larger family members and therefore offers true condensate separation values for the smaller compressor applications.

Product features:

- Separation of mineral lubricants.
- Separation of synthetic lubricants.
- Any type of drain can be applied.

Commercial advantages:

- No de-rating or complicated sizing charts.
- Compact design
- Easy serviceable/maintenance
- Clothing kit included
- Test kit included

Specifications:

Target output value	<10 ppm
Inlet connections	1/2"
Outlet connection	1/2"
Test valve	yes
Housing material	PE
Total recyclable	yes



All PURO models can accept condensate discharge from intelligent drains, timer drains, float drains and manual drains. Additional condensate can be added manually.

Consult factory for: **Larger compressor capacities.**
 *** Special Polyglycol applications.**

Information provided herewith is believed to be accurate and reliable. However, no responsibility is assumed for its use or for any infringement of patents or rights of others, which may result from its use. In addition, the manufacturer reserves the right to revise information without notice and without incurring any obligation.

JORC Industrial BV	Tel	+31 45 524 24 27
Pretoriastraat 28	Fax	+31 45 524 19 79
NL-6413 NN Heerlen	E-mail	info@jorc.nl
The Netherlands	http://	www.jorc.nl